March 12 - 14 2002

Duane Smith

Combustion Manager
Industrial Engine Programs
Rolls-Royce Corporation
Indianapolis, IN




Overview topics

- Low emission combustion system enhancement for 501-K industrial engine by integrating ATS technologies
- Dual-fuel technology assessment
- Low emission combustion technology development with wide operating range



- Low emission combustion system enhancement for 501-K industrial engine by integrating ATS technologies
 - Refinements in premixer aerodynamics
 - Improvements in liner and transition wall cooling design
 - Adjustments of the stoichiometry in the pilot fuel region




Benefits

- Improved durability / better emission control over combustor's life cycle
- Improved operability and turndown performance
- Production release of enhanced 501-K low emission combustion system targeted for 2002




- Enhanced cooling for improved durability
 - Wall temperature levels and thermal gradients reduced
 - Liner Barrel
 - Optimization of cooling flow lowered wall temperatures 100°F
 - Transition Liner
 - Replace conventional film cooling with targeted effusion cooling






Refined aerodynamics for better mixing and lower emissions




Production Standard Premixer



Improved Premixer



- Dual-fuel technology development
 - Liquid fuel integration into 501-K premixer




Liquid fuel injection through spokes



Rig testing demonstrated 60 ppm NOx capability on diesel fuel



- Dual-fuel technology development
 - Advanced concept module



Flame pattern burning diesel fuel




Cross-sectional view

Rig testing demonstrated 45 ppm NOx capability on diesel fuel




Two-stage, radial inflow combustion system for next-generation DLE



- Benefits:
 - Single-digit emissions over a wide range of operating temperatures
 - Common architecture for easy integration into 601-K, RB211, and Trent platforms





 ATS two-stage burner significantly expands the low emission operational window to permit single-digit operation from baseload down to 30% power




 Developed a radial inflow premixer to prepare the f/a mixture and establish aerodynamics for stable burning

Premixng Performance









Flame structure burning natural gas fuel



- Developed a tubular mixer that produces superior f/a uniformity
 - Tube Premixer Analysis
 - Primary/Secondary Jets
 - Mixing Method
 - Through the Tube










 An independent corporate funded program validated excellent emission performance under 20 atmosphere pressure conditions



ATS-3 combustor partially mounted in high pressure test facility

Conclusions from the ATS-3 combustor evaluation

- Stable, quiet burning can be achieved at low emission levels with lean premixed combustion
- Low emissions can be maintained over a wide temperature range

Future activity in 2002

- Explore full range of operation at different inlet conditions for candidate engine applications
- Investigate tolerance to various integration approaches



Summary of progress

- Improved the existing 501-K product line by incorporating ATS technologies
- Gathered experience and technology for dual-fuel applications:
 - Introduction of dual-fuel capability provides broader market appeal, leading to more customers with low emission engines
 - Established foundation for adapting the dry low emission combustion system to multi-fuel applications
 - Provided base technology to support future dual-fuel combustion system designs
- Developed and demonstrated system level, single-digit, low-emission combustion technology for near-term products. Application of this technology in the industrial Trent, RB211, or 601-K would result in very low emissions over a very wide range of engine operating conditions